

EU - TYPE EXAMINATION CERTIFICATE

Equipment or Protective System Intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU

- 1
- 2
- 3 EU - Type Examination Certificate Number: **Baseefa16ATEX0182X – Issue 2**
- 4 Product: **Vib Meter Type 9080-Ex**
- 5 Manufacturer: **Synatel Instrumentation Limited**
- 6 Address: **Walsall Road, Norton Canes, Cannock, Staffordshire, WS11 9TB**
- 7 This re-issued certificate extends EU Type Examination Certificate No. Baseefa16ATEX0182X to apply to product designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.
- 8 SGS Baseefa, Notified Body number 1180, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.
- The examination and test results are recorded in confidential Report No. **See Certificate History**
- 9 Compliance with the Essential Health and Safety Requirements has been assured by compliance with:
EN 60079-0:2012+A11: 2013 EN 60079-11: 2012
except in respect of those requirements listed at item 18 of the Schedule.
- 10 If the sign “X” is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.
- 11 This EU - TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by this certificate.
- 12 The marking of the product shall include the following :
- (Ex) II 2G Ex ib IIC T4 Gb (-20°C ≤ Ta ≤ +40°C)**

SGS Baseefa Customer Reference No. **1057**

Project File No. **18/0274**

This document is issued by the Company subject to its General Conditions for Certification Services accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and the Supplementary Terms and Conditions accessible at <http://www.sgs.com/SGSBaseefa/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. It does not necessarily indicate that the equipment may be used in particular industries or circumstances. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, schedule included, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Baseefa Limited

Rockhead Business Park, Staden Lane,
Buxton, Derbyshire SK17 9RZ

Telephone +44 (0) 1298 766600 Fax +44 (0) 1298 766601
e-mail baseefa@sgs.com web site www.sgs.co.uk/sgsbaseefa
Registered in England No. 4305578.

Registered address: Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN



R S SINCLAIR
TECHNICAL MANAGER
On behalf of SGS Baseefa Limited

13

Schedule

14

Certificate Number Baseefa16ATEX0182X – Issue 2

15 Description of Product

The Vib Meter Type 9080-Ex is a vibration meter that can be used to take measurements of vibration using a cable connected (intrinsically safe) accelerometer. The vibration meter is capable of displaying vibration in a variety of different formats such as overall values of acceleration, velocity or displacement, frequency spectra or vibration in various frequency bands centred on multiples of a machine's running speed for example.

The vibration meter comprises a handheld unit with processor PCB, Bluetooth® module, LCD display and keypad. The keypad is used to initiate readings and navigate through the various different vibration display formats.

The unit is battery powered using two Energizer L91 type AA cells, which may only be changed in the non-hazardous area, that are fitted via a battery compartment lid that is attached by 6 screws to the rear of the instrument.

The only electrical connection that can be made to the vibration meter is the connection of an intrinsically safe accelerometer via an integral BNC connector.

The accelerometer BNC connector has the entity parameters:

$$U_o = 21.42V$$

$$I_o = 75mW$$

$$P_o = 400mW$$

$$C_i = 0$$

$$L_i = 0$$

$$C_o = 100nF$$

$$L_o = 3mH$$

16 Report Number

See certificate history

17 Specific Conditions of Use

1. The elastomeric boot shall be fitted to the instrument at all times when used in the hazardous area

18 Essential Health and Safety Requirements

In addition to the Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9, the following are considered relevant to this product, and conformity is demonstrated in the report:

Clause	Subject
1.2.7	LVD type requirements
1.2.8	Overloading of equipment (protection relays, etc.)
1.4.1	External effects
1.4.2	Aggressive substances, etc.

19 Drawings and Documents

New drawings submitted for this issue of certificate:

Number	Sheet	Issue	Date	Description
A4-15892A	1 of 1	0	06/04/2018	Vib Mon AIN Boot Label
A4-15893A	1 of 1	1	30/07/2018	Vib Mon AIN Rear Label

Drawings A4-15871A and A4-301503A have been superseded by the above drawings.

Current drawings which remain unaffected by this issue:

Number	Sheet	Issue	Date	Description
M-200844A	1 of 1	0	23/02/2017	I.S. Protection Circuit Assembly - Parts List
A4-200844A	1 of 1	0	28/07/2015	I.S. Protection Circuit Assembly - Schematic
A3-200845A/1	1 of 1	0	24/01/2017	I.S. Protection Circuit Assembly – Top Component Ident
A4-200845A/2	1 of 1	0	24/01/2017	I.S. Protection PCB - Component Side Copper
A3-200845A/7	1 of 1	0	24/01/2017	I.S. Protection Circuit Assembly – Bottom Component Ident
A4-200845A/8	1 of 1	0	24/01/2017	I.S. Protection PCB – Non-component Side Copper
A3-301491A	1 of 1	0	17/01/2017	TPI Bottom Case Dimensions
A3-301492A	1 of 1	0	17/01/2017	TPI Top Case Dimensions
A4-301493A	1 of 1	0	17/01/2017	TPI Battery Cover Dimensions
A4-301494A	1 of 1	0	17/01/2017	TPI BNC Housing Dimensions
A4-301495A	1 of 1	0	17/01/2017	TPI Lock Ring Dimensions
A3-301496A	1 of 1	0	17/01/2017	TPI Front Label and Keypad Dimensions
A3-301499A	1 of 1	0	17/01/2017	TPI Boot Dimensions
A4-301500A	1 of 1	0	03/02/2017	TPI Base Machining
A4-301501A	1 of 1	0	24/01/2017	TPI Top Machining
A3-301502A	1 of 1	0	01/02/2017	ATEX TPI Vibration Monitor
400026	1 of 1	A	31/01/2017	BOM for Battery Protection
A4-400026A	1 of 1	0	12/01/2017	Battery Protection - Schematic
A4-400027A/1	1 of 1	0	12/01/2017	Battery Protection – Assy – Component layout
A4-400027A/2	1 of 1	0	12/01/2017	Battery Protection – Assy – Copper

All the above drawings are also associated and held with IECEx BAS 16.0131X.

20 Certificate History

Certificate No.	Date	Comments
Baseefa06ATEX0182X	15 March 2017	The release of the prime certificate. The associated test and assessment against the requirements of EN 60079-0:2012+A11:2013 and EN 60079-11:2013 are documented in Test Report No. GB/BAS/ExTR16.0397/00, Project Number 14/0312.
Baseefa16ATEX0182X Issue 1	18 July 2018	To permit the fitting of a Bluetooth® module. The associated test and assessment against the requirements of EN 60079-0:2012+A11:2013 and EN 60079-11:2013 are documented in Test Report No. GB/BAS/ExTR16.0397/01, Project Number 18/0338
Baseefa16ATEX0182X Issue 2	15 August 2018	To permit the fitting of alternative marking labels that detail the US/C marking in addition to the IECEx & ATEX marking. The associated test and assessment against the requirements of EN 60079-0:2012+A11:2013 and EN 60079-11:2013 are documented in Test Report No. GB/BAS/ExTR17.0201/00, Project Number 18/0274

For drawings applicable to each issue, see original of that issue.